

Expanding Technology™


POLYGRID[®] EXPANDED POLYMERS FOR MEMBRANE SUPPORT

Applications & Advantages

- ▲ Membrane Support, Separation Backing and Purification
- ▲ Assures Media Integrity & Pleat Spacing Even Under Dynamic Flow
- ▲ Reduced Thickness Increases Filter Surface Area
- ▲ Materials Laminate for Contraction, Co-Expansion and Flex with Filter Membranes

Filtration and Separation are key criteria for industries that process water, food & beverages, chemicals, and pharmaceuticals. Dexmet custom manufactures all PolyGrid[®] materials in a multitude of open area designs with controlled pore sizes to provide a more consistent flow rate for your filter and separation applications.

Dexmet offers the greatest range of products, capabilities and resources available... all with ISO 9001:2008 certified quality.




Features

- ▲ Pore Size and Thickness Down to 25 Microns
- ▲ 1300+ Openings/cm² (8500+ Openings/inch²)
- ▲ Widths to 1200 mm

Common Polymers

PTFE, PP, PE, PCTFE, PFA, ECTFE, PET, CPET, PEEK, Nylon, Polysulfones and Custom Plastics




DEXMET CORPORATION
22 BARNES INDUSTRIAL ROAD SOUTH
WALLINGFORD, CT 06492 • USA

VISIT OUR WEBSITE FOR MORE INFORMATION
WWW.DEXMET.COM
+1-203-294-4440

PRECISION EXPANDED POLYMERS FOR FILTRATION, SEPARATION AND CHEMICAL PROCESSING APPLICATIONS

Standard Dexmet PolyGrid® Configurations

Tool Code	LWD (mm)	SWD (mm)		Hole Size (mm)		Opening/SQCM		Open Area		Width (mm)	Raw Thickness (mm)	
		Min	Max	Min	Max	Min	Max	Min	Max		Min	Max
020	0.508	0.279	0.330	0.025	0.178	1162.79	1395.35	32%	75%	203.2	0.025	0.051
025	0.635	0.318	0.391	0.030	0.203	806.20	992.25	32%	75%	203.2	0.025	0.076
031	0.787	0.457	0.610	0.038	0.254	410.85	550.39	32%	82%	304.8	0.025	0.127
040	1.016	0.559	0.813	0.051	0.432	271.32	348.84	24%	85%	304.8	0.038	0.152
050	1.270	0.610	0.914	0.076	0.559	173.64	254.26	21%	89%	609.6	0.038	0.203
060	1.524	0.762	1.092	0.076	0.686	120.93	178.29	20%	90%	609.6	0.038	0.229
075	1.905	0.762	0.940	0.084	0.762	111.63	136.43	15%	90%	965.2	0.038	0.229
077	1.956	0.838	1.422	0.102	0.838	73.64	120.16	15%	90%	914.4	0.051	0.305
080	2.032	0.940	1.702	0.178	1.016	58.14	104.65	16%	90%	1219.2	0.051	0.356
090	2.286	1.143	1.422	0.178	1.143	62.02	77.52	16%	90%	609.6	0.051	0.356
100	2.540	1.016	1.956	0.178	1.168	38.76	73.64	16%	90%	965.2	0.051	0.432
105	2.667	1.270	1.956	0.178	1.219	38.76	54.26	20%	90%	609.6	0.051	0.457
125	3.175	1.270	2.819	0.203	1.321	23.26	50.39	20%	90%	1219.2	0.051	0.635
140	3.556	1.499	3.175	0.254	1.651	17.05	38.76	30%	90%	609.6	0.076	0.762
158	4.001	1.956	3.175	0.279	1.905	15.50	27.91	30%	90%	685.8	0.076	0.762
180	4.572	1.803	2.819	0.279	2.032	15.50	23.26	32%	90%	609.6	0.102	0.762
190	4.826	1.702	2.540	0.508	2.235	12.40	20.16	35%	90%	609.6	0.127	0.762
215	5.461	2.108	3.632	0.508	2.413	10.08	17.05	35%	90%	609.6	0.127	0.762
236	5.994	2.311	3.632	0.635	2.540	9.30	13.95	35%	90%	609.6	0.127	0.762
250	6.350	2.540	4.424	0.686	2.794	7.75	12.40	35%	90%	609.6	0.127	0.762
284	7.214	2.311	3.632	0.762	3.302	6.98	12.40	35%	90%	609.6	0.127	0.762
400	10.160	3.175	8.458	0.889	4.572	2.33	6.20	35%	90%	609.6	0.127	0.762
500	12.700	2.311	3.632	0.762	3.302	6.98	12.40	35%	90%	609.6	0.127	0.762



Corporate Sponsor:
Society For The Advancement of
Material and Process Engineering



Corporate Sponsor:
American Filtration &
Separations Society

▲ ISO 9001:2008 Certified ▲ Class 10,000 Clean Room Manufacturing ▲ 6,000 Sq/Meter Facility

DEXMET CORPORATION
22 BARNES INDUSTRIAL ROAD SOUTH
WALLINGFORD, CT 06492 • USA

VISIT OUR WEBSITE FOR MORE INFORMATION
WWW.DEXMET.COM
+1-203-294-4440

POLYGRID® IS A REGISTERED TRADEMARK OF DEXMET CORPORATION. EXPANDING TECHNOLOGY™ IS A TRADEMARK OF DEXMET CORPORATION